

## **SAFETY DATA SHEET**

### FERROCOTE<sup>™</sup> 61A US

SDS according to the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200), Revision 2012

Section 1. Identification		
Product code	: 007734-24	
Product name	: FERROCOTE™ 61A US	
Other means of identification	: Not available.	
Relevant identified uses o	f the substance or mixture and uses advised against	
Relevant uses	: Corrosion inhibitor	
Uses advised against	: Any other purpose.	
Supplier	<ul> <li>Quaker Houghton PA, Inc. 901 E. Hector Street Conshohocken, PA 19428 USA T: 610-832-4000</li> <li>Wallover Oil Company 21845 Drake Road Strongsville, OH 44149 USA www.wallover.com T: (440) 238-9250</li> <li>ProductStewardship@quakerhoughton.com www.quakerhoughton.com</li> </ul>	
Emergency telephone number (with hours of operation)	: CHEMTREC US/Canada:1-800-424-9300 or 1-703-527-3887 (24 hours)	

### Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous (29 CFR 1910.1200).	by the OSHA Hazard Communication Standa	ard
Classification of the substance or mixture	: SKIN SENSITIZATION - Category 1		
<u>GHS label elements</u> Hazard pictograms			
Signal word	: Warning		
Date of issue/Date of revision	: 1 November 2021	Version :1	1/10

### Section 2. Hazards identification

Hazard statements	: May cause an allergic skin reaction.
Precautionary statements	
Prevention	: Wear protective gloves. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.
Response	: Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water.
Storage	: Not applicable.
Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> </ul>
Hazards not otherwise classified	: None known.

### Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated heavy naphthenic	≥90	64742-52-5
Mineral oil	≤3	-
Sulfonic acids, petroleum, calcium salts, overbased	≤3	68783-96-0

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

The exact percentage (concentration) of composition has been withheld as a trade secret

### Section 4. First aid measures

Description of necessar	<u>y first aid measures</u>
General advice	: Get medical attention. If medical advice is needed, have product container or label at hand. Use personal protective equipment as required. Remove contaminated clothing and wash it before reuse. Wash skin surfaces thoroughly after contact.
Inhalation	<ul> <li>Move affected person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention.</li> </ul>
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and wash it before reuse. Get medical attention if symptoms occur.
Eye contact	<ul> <li>Flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Remove contact lenses, if present and easy to do.</li> </ul>
Ingestion	: Ingestion may cause gastrointestinal irritation and diarrhea. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
Most important sympton	ns and effects, both acute and delayed
Inhalation	: Not expected under normal use.
Skin contact	: irritation,redness,skin rash or hives
Eye contact	: Not expected under normal use.
Ingestion	: Not expected under normal use.
Indication of immediate	medical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically.
Specific treatments	: No specific treatment.

### Section 4. First aid measures

# **Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Use personal protective equipment as required.

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire. Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: In a fire, hazardous decomposition products may be produced. carbon oxides (CO, CO <sub>2</sub> ) nitrogen oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Put on appropriate personal protective equipment (see Section 8). Keep unnecessary personnel away. Avoid breathing vapor or mist. Provide adequate ventilation.	
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". Evacuate area.	
Environmental precautions	: Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Do not allow any potentially contaminated water, including rain water, runoff from fire fighting or spills, to enter any waterway, sewer or drain.	
Methods and materials for co	ntainment and cleaning up	
Small spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	: Stop leak if without risk. Move containers from spill area. For large spills, dike spilled material or otherwise contain it to ensure runoff does not reach a waterway. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	

### Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
Storage temperature	:	Storage temperature: 4 to 40°C (39.2 to 104°F).
Shelf life	:	12 months

### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy naphthenic	ACGIH TLV (United States, 3/2019). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist OSHA PEL (United States, 5/2018). TWA: 5 mg/m <sup>3</sup> 8 hours.
Mineral oil	OSHA PEL (United States). TWA: 5 mg/m <sup>3</sup> NIOSH REL (United States). TWA: 5 mg/m <sup>3</sup> NIOSH REL (United States, 10/2016). TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist ACGIH TLV (United States). STEL: 10 mg/m <sup>3</sup> 15 minutes. TWA: 5 mg/m <sup>3</sup> 8 hours.
Sulfonic acids, petroleum, calcium salts, overbased	None.

Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

### Section 8. Exposure controls/personal protection

	· · ·
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Keep equipment clean.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.
Other skin protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: A respirator is not needed under normal and intended conditions of product use. Use appropriate respiratory protection if there is a risk of exceeding any exposure limits.
Thermal hazards	: Not expected under normal use. Not relevant/applicable due to nature of the product.

### Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Clear. Amber.
Odor	: Pleasant.
Odor threshold	: Not available.
рН	: Not available.
Melting point	: Not available.
Boiling point	: 235°C (455°F)
Flash point	: Open cup: 193°C (379.4°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 0.899
Solubility	: Insoluble in the following materials: cold water.
Solubility in water	: Not available.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.

FERROCOTE™ 61A US	007734-24	
Section 9. Physical and chemical properties		
Decomposition temperature	: Not available.	
Viscosity	: Kinematic (40°C (104°F)): 0.22 cm²/s (22 cSt)	
VOC content		
Product	: 0.44 lbs/gal ASTM D2369	
Section 10. Stabil	ity and reactivity	
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
Chemical stability	: The product is stable.	
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
Conditions to avoid	: No specific measures identified.	
Incompatible materials	: Strong oxidizing materials. strong acids. strong alkalis	
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

### **Section 11. Toxicological information**

#### Information on toxicological effects

Acute toxicity

: Based on available data, the classification criteria are not met.

Acute toxicity estimates Not available.

Numerical measures of toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 Dermal	Rabbit	>2000 mg/kg	-
Sulfonic acids, petroleum, calcium salts, overbased	LD50 Oral LD50 Oral	Rat Rat	>5000 mg/kg >5 g/kg	-

Irritation/Corrosion : Based on available data, the classification criteria are not met.

Product/ingredient name	Result	Species	Score	Exposure	Observation
Distillates (petroleum), hydrotreated heavy naphthenic	Skin - Severe irritant	Rabbit	-	500 mg	-
Sensitization	: May cause sensitization	n by skin contact			
Mutagenicity	: Based on available data	a, the classificati	on criteria are	e not met.	
Carcinogenicity	: Based on available data	a, the classificati	on criteria are	e not met.	
Reproductive toxicity	: Based on available data	a, the classificati	on criteria are	e not met.	
Specific target organ toxicit	ty (single exposure) :	Based on availa	ble data, the o	classification crite	eria are not met.

### Section 11. Toxicological information

Specific target organ toxicity (repeated

: Based on available data, the classification criteria are not met.

exposure)	
Aspiration hazard	

: Based on available data, the classification criteria are not met.

Name		Result
Mineral oil		ASPIRATION HAZARD - Category 1
Other information	: None identified.	

#### Information on the likely routes of exposure

Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause sensitization by skin contact.
Eye contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

#### Delayed and immediate effects and also chronic effects from short and long term exposure None identified.

#### Symptoms related to the physical, chemical and toxicological characteristics

Inhalation	: Not expected under normal use.
Skin contact	: irritation,redness,skin rash or hives
Eye contact	: Not expected under normal use.
Ingestion	: Not expected under normal use.

### Section 12. Ecological information

This material is harmful to aquatic life with long lasting effects.

#### <u>Toxicity</u>

Not available.

#### Persistence and degradability

#### **Bioaccumulative potential**

Not available.

#### Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### Disposal methods

: Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Empty containers or liners may retain some product residues. Empty containers retain product residue and can be hazardous. Care should be taken when handling emptied containers that have not been cleaned or rinsed out.

### Section 14. Transport information

	DOT Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

#### Additional information

# **Special precautions for user : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

### Section 15. Regulatory information

#### U.S. Federal regulations

#### Clean Water Act (CWA) 311

None of the components are listed.

#### Clean Water Act (CWA) 307

None of the components are listed.

#### Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)

None of the components are listed.

#### CERCLA: Hazardous substances.

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

**Reportable quantity** : methanol: 5000 lbs. (2270 kg); 2,2'-iminodiethanol: 100 lbs. (45.4 kg);

#### SARA 302/304

None of the components are listed.

### Section 15. Regulatory information

#### SARA 311/312

```
Classification
```

: See GHS Classification in section 2 for hazard class information

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

State regulations	
Massachusetts	: The following components are listed: OIL MIST, MINERAL
New York	: None of the components are listed.
New Jersey	: None of the components are listed.
Pennsylvania	: None of the components are listed.
California	

#### California Prop. 65

Ingredient name	Concentration	
Coconut oil diethanolamine condensate	<1	Cancer
Diethanolamine	Trace	Cancer
Methanol	Trace	Developmental

#### SCAQMD Rule 1144

The sale or distribution in the SCAQM District of California for metal working fluids or direct-contact lubricants is allowed if EITHER the VOC of the product itself OR the VOC of the diluted product at the point of use is less than the following limits: (1) 75 g VOC/L for metal forming, metal removal, metal treating; (2) 50 g VOC/L for metal protection, direct-contact lubricant. The VOC of this product as sold is:

Product as-supplied : 0.49 g/l ASTM E1868-10 (2021)

#### International regulations

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### Inventory list

United States Canada

- : All components are active or exempted.
- : All components are listed or exempted.

### Section 16. Other information

Date of issue/Date of revision	: 11/1/2021
Version	: 1
	Quaker Houghton Product Stewardship
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations VOC = Volatile Organic Compound
References	: Safety data sheets of raw materials, global regulatory body information, scientific literature, and testing data .

#### Indicates information that has changed from previously issued version.

#### Notice to reader

This product's safety information is provided to assist our customers in assessing compliance with safety/health/ environmental regulations. The information contained herein is based on data available to us and is correct to the best of our knowledge, information and belief at the date of its publication. However, no warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of this data, the results to be obtained from the use thereof, or the hazards connected with the use of the product. Since the use of this product is within the exclusive control of the user, it is the user's obligation to determine the conditions for safe use of the product. Such conditions should comply with all regulations concerning the product. The company referenced in this Safety Data Sheet assumes no liability for any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is attributable to the gross negligence of such company.